

SAFETY INSTRUCTIONS

KEEP OUT OF REACH OF CHILDREN

CAUTION: May cause eye and skin irritation on contact. Do not take internally.

Although EAZY STRIP is not as corrosive as many commonly used finish removers, be sure to wear a long sleeved shirt, rubber gloves and eye protection during use. **If exposed**, flush eyes with plenty of water for at least 15 minutes and wash skin with soap and water. **If swallowed**, do not induce vomiting. Give one or two glasses of water and immediately call a physician. Maintain adequate ventilation in confined areas. **If spraying**, use a NIOSH approved chemical cartridge (organic vapor) respirator. Rinse down plants, shrubs, and grass with plenty of water if EAZY STRIP comes in contact with them.

EAZY STRIP™

Professional Finish Remover

EAZY STRIP Professional Finish Remover is an environmentally friendly, water-based solvent that removes most oil and water based stains and topcoats. EAZY STRIP contains no harsh chemicals, is biodegradable and non-flammable and, unlike caustic strippers, EAZY STRIP will not darken nor discolor the wood.

**STIR WELL
BEFORE
USE**

INGREDIENTS:	CAS #
Benzyl alcohol	100-51-6
N-methyl-2 pyrrolidone	872-50-4
Formic acid	64-18-6
Water	7732-18-5
Proprietary filler	N/A

WARNING: This product contains a chemical known to the State of California to cause reproductive toxicity.

VOC: 100 g/l max.

DIRECTIONS FOR USE

COVERAGE RATE: Always test a small section before using EAZY STRIP on the entire wall. Use a scraper to see if the finish has softened enough to remove. In order for EAZY STRIP to work, coverage should not exceed 50 square feet per gallon. It must be applied in a thick layer. EAZY STRIP can be used on a variety of surfaces including wood, plaster, concrete, stone, metal and fiberglass. **Do not use EAZY STRIP on sheetrock, plastic, rubber or linoleum surfaces. Caution: prolonged contact with EAZY STRIP will soften synthetic chinking, caulks and sealants.** While pressure washing, avoid applying high pressure directly on any sealants.

EQUIPMENT: Safety equipment, bucket, brush or roller, paint scraper, rags, and a pressure washer capable of generating at least 500 to 600 psi. For the most efficient removal of the finish, use a pressure washer with an output of three gallons per minute or greater and a 15 degree fan tip nozzle.

APPLICATION INSTRUCTIONS

STIR WELL BEFORE USE. EAZY STRIP works best when applied at temperatures between 60°F and 80°F and try to avoid working in direct hot sunlight. Work on small sections (50 square feet or so) at a time. Apply a layer of EAZY STRIP at least 1/8" thick to finished surfaces using a brush or roller with a 1/2" nap. When removing a finish from a wall, start at the bottom of the wall and work your way up. Allow the EAZY STRIP to remain on the surface for at least 30 to 60 minutes. The removal of multiple coats of stain or some types of finishes may require longer contact time, especially in cooler weather. It is acceptable if EAZY STRIP forms a surface crust but if the temperature is above 90°F or if the wall is in direct sunlight, a light misting with water will help keep it active. Performance varies with weather conditions.

Once the finish has softened, remove it with a pressure washer. If EAZY STRIP has been on a wall for over 30 minutes, be careful not to apply too much pressure to chinking or sealants. On walls, pressure wash starting at the top of the area and work your way down. If there are areas where pressure washing has not removed all of the finish, try scraping off the remaining finish with a paint scraper or stiff nylon bristle brush while the finish is still soft. Protected areas under porch roofs, soffits, etc. may occasionally require a second application to remove all of the finish.

Once the finish removal process is completed, be sure to thoroughly rinse the surface in order to remove any EAZY STRIP residue and return the wood to its proper pH balance.

CLEAN UP

Use soap and water to clean tools and equipment.

STORAGE

Store Eazy Strip out of direct sunlight and protect from freezing. Although Eazy Strip is freeze-thaw stable, if the product is accidentally frozen, allow to thaw and check for suitability of use before applying.

LIMITED WARRANTY

Perma-Chink Systems, Inc. warrants and represents that Perma-Chink Systems Family of Products will conform to the description and specifications previously set forth and be free from defects in material and workmanship when shipped to the buyer. EXCEPT WHEN HEREIN EXPRESSLY STATED, THERE ARE NO WARRANTIES, EXPRESS OR IMPLIED, BY OPERATION OF LAW OR OTHERWISE, APPLICABLE TO THE PERMA-CHINK LOG HOME PRODUCT. PERMA-CHINK SYSTEMS EXPRESSLY DISCLAIMS ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.



Eastern Division
1-800-548-3554

Western Division
1-800-548-1231

Colorado
1-800-433-8781

Montana
1-800-479-7090

Minnesota
1-877-244-6548

Sevierville, TN
1-865-774-3307

**Net Contents: 5.0 gallons
(approx. 18.9 liters)**

11/06