

# OXcon™

## Blonding Agent

**Mix one (1) part OXcon with four (4) parts water for use.**

OXcon is an easy to use blonding agent designed to brighten up wood surfaces of both exterior and interior logs, deck boards, railings and fences. This powerful blonding agent works to return gray weathered wood to its natural golden color prior to using water-resistant finishes or semi-transparent stains. OXcon contains oxalic acid that works to revive your woodwork, giving the wood a fresh, natural look.

OXcon is especially recommended after the use of some chemical strippers. Remember to rinse thoroughly between applications and read and follow the directions for use.

**PERMA-CHINK®  
SYSTEMS, INC.**

[www.permachink.com](http://www.permachink.com)

1.0 gallon (approx. 3.8 liters)

8/04

### APPLICATION DIRECTIONS

**Surface Preparation:** Brush or wipe off any extraneous debris that may be present. OXcon should only be applied to clean, bare wood surfaces.

**Mixing:** Dilute one (1) part OXcon with four (4) parts water in a clean plastic container. *Do not use a metal container!* OXcon must be properly diluted since higher concentrations can damage the wood surface. Mix thoroughly before using and periodically during use.

**Application:** OXcon may be applied with a low pressure sprayer, roller, brush, or broom. Use liberal amounts (a flooding coat) over an entire area. Do not spot-treat since this method of application can cause blotching. Allow the solution to remain on the surface for 10 to 15 minutes, then rinse thoroughly with lots of fresh water starting at the top of the wall and working your way down. Allow the surface to dry, then look at the results. If the wood is still too dark or blotchy, repeat the procedure.

#### CAUTION

Keep out of reach of children. Wear protective breathing gear, rubber gloves, and eye protection. Make certain the work area is well ventilated. Do not breathe fumes and keep away from heat that could produce fumes. If exposed, promptly flush eyes with water and wash skin with soap and water. Cover plants, shrubs, aluminum frames, etc. before use.

#### LIMITED WARRANTY

Perma-Chink Systems, Inc. warrants and represents that Perma-Chink Systems Family of Products will conform to the description and specifications previously set forth and be free from defects in material and workmanship when shipped to the buyer. EXCEPT WHEN HEREIN EXPRESSLY STATED, THERE ARE NO WARRANTIES, EXPRESS OR IMPLIED, BY OPERATION OF LAW OR OTHERWISE, APPLICABLE TO THE PERMA-CHINK LOG HOME PRODUCT. PERMA-CHINK SYSTEMS EXPRESSLY DISCLAIMS ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

**PERMA-CHINK®  
SYSTEMS, INC.**

[www.permachink.com](http://www.permachink.com)

**Eastern Division**      **Western Division**  
1-800-548-3554      1-800-548-1231

**Colorado**      **Montana**      **Minnesota**  
1-800-433-8781      1-800-479-7090      1-877-244-6548

8/04