

### APPLICATION DIRECTIONS

1. Surfaces must be clean, dry and free of mold, dirt, etc. (When using on logs they must be properly cured.)
2. Apply caulk with even steady pressure and fill the joint completely. QSL will fill gaps ½" wide by ¼" deep quite well. For larger and deeper joints use backer rod before caulking.
3. Once applied, smooth bead with moistened sponge, brush or cloth. Be sure to finish all caulking / sealing prior to painting or staining. Cleanup is with soap and water. Allow proper curing time (generally 4 to 6 hours, depending on weather conditions), before applying any paint or stain.
4. Apply only when QSL and surface temperatures are between 40°F and 120°F. Do not apply if rain is expected within the next 24 hours.

**IMPORTANT:** QSL Log Home Sealant is not intended for underwater use.

**CAUTION! Do not take internally.  
KEEP OUT OF REACH OF CHILDREN.**

**DURABLE**

**FLEXIBLE**

**PROFESSIONAL 230 GRADE**



## Exterior / Interior Log Home Sealant

QSL Advance Technology Log Home Sealant is today's premier sealant for most caulking applications around all types of homes. QSL Log Home Sealant provides weather and water protection while stretching and flexing to allow for building movement. QSL Log Home Sealant adheres to common building surfaces such as wood, metal, concrete, brick, masonry, porcelain, ceramic tile, marble and glass. Ideal for sealing construction joints to logs, windows and doors, woodwork, eaves, soffits, tubs, sinks, showers, vents, expansion joints – anywhere a permanent flexible seal is needed. QSL Advanced Technology Log Home Sealant meets the performance requirements of Federal Specification TT-00230C, Type II, Class A and ASTM Spec. C-920, Class 25. It also exceeds ASTM Spec. C-834.

**LIMITED 50 YEAR WARRANTY:** If this material peels, cracks or separates when applied as directed within fifty years after application, it will be replaced without charge upon presentation of proof of purchase, and this container. This guarantee only applies to residential use. All damage including consequential damage or other remedies, are excluded. No other warranties apply (including fitness for a particular purpose).

**PERMA-CHINK®**  
**SYSTEMS, INC.**  
[www.permachink.com](http://www.permachink.com)

**11 oz. (325 ml)**

Eastern Division  
1-800-548-3554

Western Division  
1-800-548-1231

Colorado  
1-800-433-8781

Montana  
1-800-479-7090

Minnesota  
1-877-244-6548

Sevierville, TN  
1-865-774-3307

Rev. 1/07