

Stack "N" Seal 2™ Log & Timber Sealant

APPLICATION DIRECTIONS

1. Surfaces must be clean, dry and free of old caulk, mold, dirt, etc. Do not apply to surfaces that are frozen or covered with ice.
2. Apply sealant with even steady pressure. For sealing gaps and joints wider than 1/2", use Backer Rod before sealing.
3. Once applied, Stack "N" Seal 2 can be tooled smooth with a trowel, moistened sponge, brush or cloth.
4. When using as an internal sealant between courses of logs, refer to your log home manufacturer's construction manual for bead size requirements and bead location.
5. Allow 4 to 6 hours curing time, depending on weather conditions, before applying any paint or stain.
6. Apply only when surface temperatures are between 40°F and 120°F. Do not apply if rain is expected within the next 24 hours.
7. Clean hands and equipment with soap and water.

Stack "N" Seal 2 Log & Timber Sealant may be used for multiple applications around log and timber homes. This smooth surfaced sealant provides weather and water protection while stretching and flexing to allow for structural movement. Stack "N" Seal 2 adheres to most common building surfaces such as wood, metal, concrete, brick, masonry, porcelain, ceramic tile, marble and glass. Ideal for use as an internal sealant between courses of logs and for sealing construction joints like window and door frames, woodwork, eaves, soffits, vents and expansion joints. Stack "N" Seal 2 will accept both paint and stain.

**CAUTION! Do not take internally.
KEEP OUT OF REACH OF CHILDREN.**

44 lbs. (20 kg.)

COLOR

- Pine #615
- Honey #625
- Tan #635
- Cedartone #645
- Brown #655
- Gray #665
- _____

Coverage per 5 gallon pail:

1/4 inch bead: 1800 feet
3/8 inch bead: 875 feet
1/2 inch bead: 450 feet

LIMITED WARRANTY

PERMA-CHINK SYSTEMS, Inc. warrants and represents that PERMA-CHINK SYSTEMS Family of Products will conform to the description and specifications previously set forth and shall be free from defects in material and workmanship when shipped to the buyer, EXCEPT AS HEREIN EXPRESSLY STATED. THERE ARE NO WARRANTIES, EXPRESSED OR IMPLIED, BY OPERATION OF LAW OR OTHERWISE. APPLICABLE TO THE PERMA-CHINK LOG HOME PRODUCT. PERMA-CHINK SYSTEMS EXPRESSLY DISCLAIMS ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

**PERMA-CHINK®
SYSTEMS, INC.**

www.permachink.com

Eastern Division
1-800-548-3554

Western Division
1-800-548-1231

Colorado
1-800-433-8781

Montana
1-800-479-7090

Minnesota
1-877-244-6548

Sevierville, TN
1-865-774-3307

MADE IN USA