

Manufacturing: 1605 Prosser Road Knoxville, TN 37914 (800) 548-3554

Lifeline Ultra-7™

Product Description: Lifeline Ultra-7[™] is our highest quality transparent wood stain enhanced with advanced polymer resin that delivers sophisticated color, unmatched durability and maximum coverage. In addition, Lifeline Ultra-7[™] is low in VOC's, water based and meets or exceeds all standards and environmental requirements in North America. After multiple exposure testing in harsh weather areas across the country Lifeline Ultra-7[™] stands out as the top-of-the-line, long lasting finish system.

Technical Data: Exterior Stain

- **Colors:** Available in nine standard colors, and unlimited custom colors.
- **Packaging:** 1 gal. container, 5 gal. pail, samples available.
- Surface Preparation: Must be applied to clean, dry surface.
- Application Temperature Range, °F: 40-90; Do not apply in direct hot sunlight.
- Application Methods: Airless Sprayer, brush
- Application Rates: 1st Coat 250 -350 ft²/gal.
- No. Coats: 1 or 2 Coats + 1 Coat Advance Gloss/Satin
- Toxicity: Non Toxic
- Shelf Life: 3 Years
- Drying Times: Dry to touch in 4-6 hours, Cures in 72 hours, however times will vary with temperature and humidity.
- Clean-Up: Soap and Water.
- % Solids: 19.0 23.0
- VOC, g/L: 61 (Regulatory Less Water)
- **Storage:** Freeze/Thaw Stable.
- Viscosity, cP, KU-2 Viscometer, 25°C: 230 300
- Density, lb./gal.: 8.40- 8.70
- Specific Gravity, SG: 1.01-1.04
- **pH:** 8.80 9.30