

LIFELINE™

Interior

For Interior Log Walls

and Ceilings

Color

- Water-based • Prevents Odor Absorption
- Low Odor • Resists Yellowing
- Easy to Apply • Soap & Water Clean Up

CAUTION - DO NOT TAKE INTERNALLY



PERMA-CHINK[®]
SYSTEMS, INC.

Eastern Division

Western Division

Colorado

Montana

Minnesota

Sevierville, TN

1-800-548-3554

1-800-548-1231

1-800-433-8781

1-800-479-7090

1-877-244-6548


1-865-774-3307

www.permachink.com

1.0 gallon (approx. 3.8 liters)

Made in USA

STIR WELL BEFORE USING



LIFELINE™ Interior Semi-Transparent Stain

STEP #1: INSPECTION

Check for deterioration and decay. Remove and replace or repair deteriorated wood. Unsound wood should be repaired prior to applying LIFELINE™ Interior.

STEP #2: SURFACE PREPARATION

All surfaces should be free from mill glaze and contaminants including dirt, dust, mold and mildew, old finishes, water repellents and wax. Use appropriate materials to clean and prepare surfaces. If a wood preservative has been previously applied, make sure it is completely dry before applying LIFELINE Interior. If the surface is tacky or there are visible deposits on the wood, wash the surface with water and allow to dry. DO NOT USE LIFELINE Interior ON SURFACES THAT HAVE BEEN BRUSHED OR RUBBED WITH STEEL WOOL. IF YOU DO, RUST SPOTS MAY APPEAR UNDER THE FINISH.

STEP #3: APPLICATION

COVERAGE RATE Coverage is approximately 350-450 square feet per gallon for the first coat and approximately 600-800 square feet per gallon for subsequent coats depending on wood type and porosity. DO NOT USE THINNERS.

STIR THOROUGHLY before and regularly during use. Wear rubber gloves to avoid stains to the skin and fingernails. If multiple containers are used on the job, they should be poured together to ensure color consistency. LIFELINE Interior can be applied with a brush or airless sprayer. Do not apply when the surface temperature of the wood is below 40° F or above 90° F. **Back brushing is required** to work the finish into the wood for optimum performance. Apply LIFELINE Interior in thin coats and always keep a "wet edge" to avoid lap marks.

Wait for the first coat to dry (at least two hours depending on temperature and humidity) before applying a second coat if desired. It is not necessary to apply two coats of LIFELINE Interior if the desired color is attained with one coat. Always back brush to ensure even coverage and to avoid visible drips and runs.

Once the LIFELINE Interior has dried and you are satisfied with the appearance, we recommend the application of Acrylic Gloss or Satin clear topcoat. These clear topcoats enhance the beauty of the finish and make the walls easier to clean. Follow the product application directions when applying any topcoat.

STEP #4: CLEANUP

Clean area and equipment immediately with warm, soapy water. For sprayers and other commercial equipment, follow the manufacturer's directions. For removing LIFELINE Interior that has dried, soften with alcohol or mineral spirits and then clean with warm water. Please do not pollute our environment. Dispose of containers and unused material in accordance with local, state, and federal regulations.

STEP #5: MAINTENANCE

Periodic cleaning with an appropriate cleaner helps extend the life of the finish and accentuates the beauty of your home. Wood checking, cracking and shrinkage may eventually expose unprotected wood. Apply periodic maintenance coats as needed.

STEP #6: STORAGE

Store LIFELINE Interior out of direct sunlight and **protect from freezing**. Although LIFELINE Interior is freeze-thaw stable, if the product is accidentally frozen, allow to thaw, mix well and check for suitability of use before applying.

Request a copy of "Caring For Your Dream Home" from any Perma-Chink Systems office for additional information about applying and maintaining LIFELINE stains and finishes.

Rev 8/06



Perma-Chink Systems, Inc. warrants and represents that Perma-Chink Systems Family of Products will conform to the description and specifications previously set forth and be free from defects in material and workmanship when shipped to the buyer. EXCEPT WHEN HEREIN EXPRESSLY STATED, THERE ARE NO WARRANTIES, EXPRESSED OR IMPLIED, BY OPERATION OF LAW OR OTHERWISE, APPLICABLE TO THE PERMA-CHINK LOG HOME PRODUCT. PERMA-CHINK SYSTEMS EXPRESSLY DISCLAIMS ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.